



FarBo® Overflow insert

Overflow insert for roof drainage systems

Applications

- Used in conjunction with FarBo roof outlets to provide an overflow roof drainage system

Key Features

- Manufactured from high quality 316 grade stainless steel
- Includes EPDM O-ring for ultimate waterproof seal
- Used in conjunction with 110mm roof outlets to provide overflow by increasing the drainage height to 25/35 mm above roof level

FarBo® Overflow insert

Code	To suit outlet diameter (mm)	Outside diameter (mm)	Overflow height (mm)
FO-OF-110	110	106	25 or 35



FO-OF

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast July 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007