



## V-Seal pipe flashings

MS Series pipe flashings

### Application

- Provides weatherseal for pipes, chimneys, flues and other penetrations through profiled sheeting or flat panel systems

### Key Features

- Square base facilitates easy installation
- Unobtrusive aesthetically pleasing solution for sealing around small pipes and cables
- Flexibility - allows for expansion, contraction and building movement
- Simple to fit sleeve marked with pipe diameters
- Life expectancy in excess of 20 years under normal weather conditions

# MS series pipe flashings

code		Pipe diameters(mm)		Base dimensions (mm)
Black EPDM Temp range -40°C to + 115°C	Red Silicone Temp range -60°C to +240°C	0-25° roof pitch	0-45° roof pitch	
MS-EB-3-25	MS-SR-3-25	3-25	3-20	80 x 80
MS-EB-5-50	MS-SR-5-50	5-50	5-45	120 x 120



**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

*©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.*



Certificate Number 10905  
 ISO 9001: 2008  
 ISO 14001: 2004  
 BS OHSAS 18001: 2007