



RyMar Cable Duct

Application

- These provide an excellent weatherproof sleeve for cables or pipes which penetrate through a flat roof.
- The two elbows direct the cables and pipes either horizontally or vertically and shelter the exit point from rain or water ingress.

Key Features

- can be supplied with two types of bends - PVC or stainless steel available with bitumen or single ply membrane flange

RyMar Cable Duct

Product Code	Base dia (mm)	Duct dia (mm)	Flange Material	Pipe Material	Duct height (mm)
RM-CD 75 PB SBS	500 x 500	75	Bitumen	PVC	350
RM-CD 75 SB SBS	500 x 500	75	Bitumen	Stainless Steel	350
RM-CD 75 PB PVC LT GREY	330 x 330	75	PVC membrane	PVC	350
RM-CD 75 PB PVC DK GREY	330 x 330	75	PVC membrane	PVC	350
RM-CD 75 SB PVC LT GREY	330 x 330	75	PVC membrane	Stainless Steel	350
RM-CD 75 SB PVC DK GREY	330 x 330	75	PVC membrane	Stainless Steel	350
RM-CD 110 PB SBS	500 x 500	110	Bitumen	PVC	380
RM-CD 110 SB SBS	500 x 500	110	Bitumen	Stainless Steel	380
RM-CD 110 PB PVC LT GREY	330 x 330	110	PVC membrane	PVC	380
RM-CD 110 SB PVC DK GREY	330 x 330	110	PVC membrane	PVC	380
RM-CD 110 SB LT GREY	330 x 330	110	PVC membrane	Stainless Steel	380
RM-CD 110 SB DK GREY	330 x 330	110	PVC membrane	Stainless Steel	380



RMCD

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007