



# StrikeClip™

Lightning clips

## Application

- For securing lightning conductor tape for roof and wall applications

## Key Features

- Unique recessed rivet to eliminate damage to the membrane
- Manufactured from high quality polymer, with excellent UV repellent properties to prevent them fading and going brittle in the sun's rays
- Easy to use - supplied as one piece product
- Accommodate a conductor strip up to 25mm wide x 5mm thick
- Supplied with 100mm x 100mm flange for securing to membrane

# Datasheet

Document Reference: DS-RP-LC-8.19/03

04 ROOFTOP DRAINAGE  
StrikeClip™ Lightning clips

# StrikeClip™ Lightning clips

Code	Flange description	Flange size (mm)	Suggested fixing centres (mm)
LC-SA	Self adhesive backing	105 x 80	500
LC-SBS-CHARCOAL	Felt - charcoal	100 x 100	500
LC-SBS-GREEN	Felt - green	100 x 100	500
LC-SBS-BRINDLE	Felt - brindle	100 x 100	500
LC-PVC-LT GREY	PVC - light grey	100 x 100	500
LC-PVC-DK GREY	PVC - dark grey	100 x 100	500
LC-EPDM	EPDM	100 x 100	500
LC *	N/A		1000 **

\* LC type is suitable for vertical applications only as it has no membrane flange.

\*\* up to 20m from ground level - 500mm thereafter - IEC 62305 standard.

Please contact our sales office for bespoke requirements.

Please apply pressure with a seam roller once installed to activate the bond.



**LC-SBS-GREEN**

**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

©Fixfast August 2019. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate number 10905  
 ISO 9001, ISO 14001  
 OHSAS 18001