



# TorVec®

Vapourseal

## Application

- Provides an airtight seal between the pipe and the vapour control layer

## Key Features

- Airtight seal prevents air leakage from the building
- Seal blocks moisture from entering the roof structure and prevents damage to the roof
- Unique rib based design – excellent adhesion to bitumen
- EPDM rubber – durable, flexible and weather proof

# Datasheet

Document Reference: DS-RP-VFRVP-7.17/01

04 ROOFTOP PRODUCTS  
TorVec® Vapourseal

| Code                                  | Pipe diameters(mm) | Base dimensions diameter(mm) |
|---------------------------------------|--------------------|------------------------------|
| Black EPDM temp range -30°C to + 90°C |                    |                              |
| TV-FR-VP-EB-50                        | 50                 | 350                          |
| TV-FR-VP-EB-75                        | 75                 | 375                          |
| TV-FR-VP-EB-110                       | 110                | 410                          |



TV-FR-VP

**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

*©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.*



Certificate Number 10905  
 ISO 9001: 2008  
 ISO 14001: 2004  
 BS OHSAS 18001: 2007