



TorVec felt roof seals[®]

Felt roof seal pipe flashings

Application

- Provides weatherseal for pipes, chimneys, flues and other penetrations through bituminous felt roof systems

Key Features

- Unique rib based design - excellent adhesion to bitumen
- EPDM rubber - durable, flexible and weatherproof
- Weathertight seal - stainless steel clamp with each pipe flashing
- Simple to fit sleeve marked with pipe diameters

Datasheet

Document reference: DS-RP-TV-7.17/01

TorVec® felt roof seals

TorVec® felt roof seals		
Code	Pipe diameters (mm)	Base diameter dimensions (mm)
Black EPDM temperature range -30°C to +90°C		
TV-FR-EB-0-40	0-49	425
TV-FR-EB-50-60	50-74	462
TV-FR-EB-75-90	75-109	492
TV-FR-EB-110-125	110-129	527
TV-FR-EB-130-140	130-149	540
TV-FR-EB-150-175	150-199	576
TV-FR-EB-200-250	200-274	637
TV-FR-EB-275-325	275-349	712
TV-FR-EB-350-400	350-489	787
TV-FR-EB-490-530	490-589	800
TV-FR-EB-590-630	590-689	900
TV-FR-EB-690-730	690-789	1000
TV-FR-EB-790-830	790-830	1100



TV-FR

TorVec® felt roof seals - retrofit		
Code	Pipe diameters (mm)	Base diameter dimensions (mm)
TV-RFR-EB-19-90	19-90	420
TV-RFR-EB-110-170	110-170	510
TV-RFR-EB-160-250	160-250	590



TV-RFR

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007