



V-Seal[®]

Strip flashing

Application

- Ideal for use on large ducting, pipework, flues and awkward flashing details

Key Features

- Roll of flexible TPE rubber strip
- Can be cut or joined to allow for use in numerous applications
- Solves problems where standard pipe flashings cannot be used
- Contains expanding aluminium strip enclosed by the TPE rubber

Datasheet

Document reference: DS-RP-VSF-7.17/01

04 ROOFTOP PRODUCTS
V-Seal[®] Strip flashing

V-Seal® Strip flashing

Dimensions			
Code	Roll dimensions (width x length)	Temperature range	Colour
SF-TG-235 x 10.0	235mm x 10m	-30°C to 115°C	Grey
SF-TG-450 x 15.0	450mm x 15m		



SF-TG

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007

V-Seal® Strip flashing

Product size selector												
Pipe diameter (mm)	MS Series		AD Series									Stripflash
	3-25	5.50	10-90	50-100	75-150	125-200	150-250	195-300	230-280	315-500	400-750	
3	✓	✓	-	-	-	-	-	-	-	-	-	-
5	✓	✓	-	-	-	-	-	-	-	-	-	-
10	✓	✓	✓	-	-	-	-	-	-	-	-	-
25	*	✓	✓	-	-	-	-	-	-	-	-	-
30	-	✓	✓	-	-	-	-	-	-	-	-	-
40	-	✓	✓	✓	-	-	-	-	-	-	-	-
50	-	*	✓	✓	-	-	-	-	-	-	-	-
60	-	-	✓	✓	-	-	-	-	-	-	-	-
70	-	-	✓	✓	-	-	-	-	-	-	-	-
80	-	-	*	✓	✓	-	-	-	-	-	-	-
90	-	-	*	✓	✓	-	-	-	-	-	-	-
100	-	-	-	*	✓	-	-	-	-	-	-	-
125	-	-	-	-	✓	✓	-	-	-	-	-	-
150	-	-	-	-	*	✓	✓	-	-	-	-	-
175	-	-	-	-	-	✓	✓	-	-	-	-	-
200	-	-	-	-	-	*	✓	✓	-	-	-	-
225	-	-	-	-	-	-	✓	✓	-	-	-	-
250	-	-	-	-	-	-	*	✓	-	-	-	-
275	-	-	-	-	-	-	-	*	✓	-	-	-
300	-	-	-	-	-	-	-	*	✓	-	-	✓
325	-	-	-	-	-	-	-	-	✓	✓	-	✓
350	-	-	-	-	-	-	-	-	✓	✓	-	✓
375	-	-	-	-	-	-	-	-	*	✓	-	✓
400	-	-	-	-	-	-	-	-	-	✓	✓	✓
425	-	-	-	-	-	-	-	-	-	✓	✓	✓
450	-	-	-	-	-	-	-	-	-	✓	✓	✓
500	-	-	-	-	-	-	-	-	-	*	✓	✓
550	-	-	-	-	-	-	-	-	-	-	*	✓
600	-	-	-	-	-	-	-	-	-	-	*	✓
650	-	-	-	-	-	-	-	-	-	-	*	✓
700	-	-	-	-	-	-	-	-	-	-	*	✓
750	-	-	-	-	-	-	-	-	-	-	*	✓

✓ = Suitable * = Suitable on lower pitches - = Not suitable

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

© Fixfast July 2017. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007