

## RyMar®

Vent pipe covers

### Application

- For the weatherproofing of soil vent pipes on new build applications

### Key Features

- A weatherproofing solution to seal the vent pipe to the roof system
- Factory bonded flange to match specific membrane material being used (material must be specified at time of order)
- These twin skin stainless steel covers provide long lasting protection concealing unsightly pipes
- The internal pipe sits within the vent pipe with an 'O' ring seal that provides an effective seal against condensation
- Adjustable cover suits pipes up to 600mm high supplied with stainless steel weather cowl to protect it against rainwater and airbourne debris


## Datasheet

Document Reference: DS-RP-VENT-7.17/01

# RyMar® Vent pipe covers

code	To suit vent pipe	Diameter of internal pipe (mm)	Diameter of outer pipe (mm)	O-ring seal diameter (mm)	Membrane attachment
RM-VENT-75-SBS	3"	58	95	10	Bituminous
RM-VENT-110-SBS	4"	87	125	8	Bituminous
RM-VENT-160-SBS	6"	145	182	5	Bituminous
RM-VENT-250-SBS	4"	87	250	8	Bituminous
	Diameter of outerskin is greater to allow for knuckles and roof level obstructions				
RM-VENT-75-PVC LT GREY	3"	58	95	10	Light grey PVC
RM-VENT-110-PVC LT GREY	4"	87	125	8	Light grey PVC
RM-VENT-160-PVC LT GREY	6"	145	182	5	Light grey PVC
RM-VENT-250-PVC LT GREY	4"	87	250	8	Light grey PVC
	Diameter of outerskin is greater to allow for knuckles and roof level obstructions				
RM-VENT-75-PVC DK GREY	3"	58	95	10	Dark grey PVC
RM-VENT-110-PVC DK GREY	4"	87	125	8	Dark grey PVC
RM-VENT-160-PVC DK GREY	6"	145	182	5	Dark grey PVC
RM-VENT-250-PVC DK GREY	4"	87	250	8	Dark grey PVC
	Diameter of outerskin is greater to allow for knuckles and roof level obstructions				

Height of vent cover above membrane level: 335 - 600mm



RM-VENT

**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

*©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.*



Certificate Number 10905  
 ISO 9001: 2008  
 ISO 14001: 2004  
 BS OHSAS 18001: 2007