



Construction foam

Application

- For standard bonding, filling, fixing and insulating

Key Features

- Single component polyurethane foam
- Cures on contact with humidity
- Forms a semi-rigid cellular structure which is weatherproof and will not rot
- Available in can with nozzle for manual application or quick and efficient screwtop gun fitting
- Temperature resistant (between -50°C and +90°C)

Construction foam

Code	Fitting	Canister size (ml)	Canisters per carton
FOAM-B3-HAND	Manual	750	12
FOAM-B3-GUN	Screwtop	750	12
FOAM-B2-HAND	Manual	750	12
FOAM-B2-GUN	Screwtop	750	12



FOAM-B2



FOAM-B3

Accessories

Code	Fitting
FOAM APPLICATOR GUN	Gun for applying foam with the screwtop fitting Robust metal construction with lockable trigger
GUN-CLEANER	Cartridge size 500ml Cleaner will dissolve uncured foam of both types Canister can be fitted to applicator gun or can be used with attached nozzle for manual spraying

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0800 304 7616 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast August 2020. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate number 10905
 ISO 9001, ISO 14001
 OHSAS 18001