

Maximum reliability. Minimum fuss.

 **FIXFAST**

Technical Data Sheet

Fire resistant construction foam

Sealing Products



Application

- + For Fire resistant bonding, filling, fixing and insulating

Key Features

- + Single component fire resistant PU foam
- + Cures on contact with humidity
- + Forms a semi-rigid cellular structure which is weatherproof and will not rot
- + Available in can with nozzle for manual application or quick and efficient screwtop gun fitting

Specification

Code	Fitting	Cartridge size (ml)	Cartridges per carton
FIREFOAM-B1-HAND	Manual	750	12
FIREFOAM-B1-GUN	Screwtop	750	12



Code	Description
FOAM APPLICATOR GUN	Gun for applying foam with the screwtop fitting Robust metal construction with lockable trigger
GUN-CLEANER	Cartridge size 500ml Cleaner will dissolve uncured foam of both types Canister can be fitted to applicator gun or can be used with attached nozzle for manual spraying



Thickness of wall (mm)	Joint dimension (mm)		Flame resistance time	
	Width	Depth	Time	Fire rating
200	11	200	229min	EI 180
200	41	200	110min	EI 90
100	30	100	50min	EI180
100	10	100	100min	EI 190
200	10	200	6 hours	-
200	20	200	6 hours	-
200	30	200	5 hours 30min	-
200	40	200	3 hours 38min	-





Merlin House
Seven Mile Lane
Borough Green
Sevenoaks
Kent
TN15 8QY

Enquiries

0845 450 7483

International

+44 (0) 1732 882387

Fax

0845 450 7486

Email

info@fixfast.com



Certificate number 10905
ISO 9001, ISO 14001
OHSAS 18001