



Cold bridging tape

CBT

Applications

- For use in liner panel applications as a thermal break

Key Features

- A cross linked, closed cell, polyethylene self adhesive foam tape
- Prevents cold bridging between mini zed purlin and the outer sheet
- Has a release paper

Cold bridging tape

Substrate							
Tape	Steel	Aluminium	GRP / PVC	Fibre cement	Glass (uncoated)	Timber (painted or stained)	Concrete / Brick-work
CBT Cold Bridge Tape**	✓	✓	●	-	●	●	○

✓ = Recommended ● = Compatible ○ = Possible **= For airseal liners, not outer sheet

Code	Roll thickness x width (mm)	Roll length (m)	Rolls per carton	Colour
CBT-4 x 38 x 20	4x38	20	7	Grey



CBT

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast July 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
 ISO 9001: 2008
 ISO 14001: 2004
 BS OHSAS 18001: 2007