



# Firestrip

## Application

- For firewall applications

## Key Features

- Intumescent strip sealant tested in accordance with BS476 Part 22 1987
- Provides 30 minute fire and smoke resistance
- Prevents vapour transmission

# Firestrip

Substrate								
Tape	Steel	Aluminium	GRP / PVC	Fibre cement	Glass (uncoated)	Timber (painted or stained)	Fire resisting	Gutter joints
Firestrip	✓	✓	✓	●	●	●	○	-

✓ = Recommended   ● = Compatible   ○ = Possible

Code	Thickness x width (mm)	Roll length (m)	Rolls per carton	Colour
FS-3 x 12 x 15	3 x 12	15	12	Off-white



**FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY**  
**T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com**

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.  
 The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

*©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.*



Certificate Number 10905  
 ISO 9001: 2008  
 ISO 14001: 2004  
 BS OHSAS 18001: 2007