



Ultra high bond tape

Application

- Suitable for use as a temporary fix when used in conjunction with structural bonding adhesives

Key Features

- When used with UHB PRIMER, provides a high strength bond within minutes of application
- Good UV resistance
- Good resistance to abrasion, corrosion and moisture
- High dielectric strength
- Excellent conformability

Ultra high bond tape

Technical Performance

Description	Units	Value	Test Method
Total Thickness	mm	0.13+0.005	GB7125-1999
Adhesive	-	Rubber	No residue
Elongation at break	%	180	GB7753-1987
Tensile strength	N/cm	22	GB7753-1987
Voltage breakdown	KV	6	EN60454-4-3-12:2006
Flammability	-	PASSED	UL510

Declaration of Conformity Information

- Conforms to BS3924 replaced by EN 60454-3-12:2006
- Conforms to EN 60454-3-12:2006
- IEC 62321:2008
- 2006/95/EC (Low Voltage Directive)
- UL510 certificated (Flame Retardant)

Storage Details

- Shelf life recommended 2 years from date of despatch at the moderate temperature and humidity environment.

Code	Roll thickness (mm)	Roll width (mm)	Roll length (m)	Rolls per carton	Colour
UHB-1.2 x 25 x 33	1.2	25	33	24	Grey
UHB PRIMER	For priming substrates prior to applying UHB-1.2 x 25 x 33				



UHB

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

*Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.
The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY*

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007