



Membrane penetration tape

Application

- Seal junctions between wood panels (eg OSB), vapour barriers and roofing barriers used in construction and renovation
- Sealing joints in cementitious boards
- Application of membranes or vapour control layers to cementitious boards
- Interior and exterior use

Key Features

- Very strong adhesion to wood panels, vapour barriers and roofing barriers
- Very good UV resistance
- Excellent resistance to aging
- Adhesion on wet surfaces
- Flexible and conformable
- Hand tearable
- Application temperature: from -10°C
- Service temperature: -40°C to +80°C

Datasheet

Document Reference: DS-W-MPT-7.17/01

07 WEATHERPROOFING
PRODUCTS
Membrane penetration tape

Membrane penetration tape

Code	Roll width (mm)	Roll length (mm)	Box Quantity
MPT-60-25	60	25	1



Membrane penetration tape

Test	Value	Unit	Standard
Thickness (without liner)	270	µm	AFERA 5006
Peel adhesion on: Stainless steel	>11	N/cm	AFERA 5001
Peel adhesion on: Barrier film*	>25	N/50mm	NF EN 12316-2
Shear resistance on: Barrier film*	>40	N/50mm	NF EN 12317-2

(*) Product meets CSTB/DIN 4108-7 specifications

(*) Tests performed on main market barrier films

To be stored at 20°C (+/-5°C) in its original package

To be used within 6 months after delivery.

FIXFAST Ltd | Merlin House | Seven Mile Lane | Borough Green | Sevenoaks | Kent | TN15 8QY
T: 0845 450 7483 | F: 0845 450 7486 | E: info@fixfast.com | W: www.fixfast.com

Fixfast is a trading name of FIXFAST Ltd which is a company registered in England & Wales with number 09481218.

The registered office is Fixfast, Merlin House, Seven Mile Lane, Borough Green, Sevenoaks, Kent, United Kingdom TN15 8QY

©Fixfast September 2017. All rights reserved. Due to a policy of continual development, Fixfast reserves the right to change product specification and descriptions without prior notice.



Certificate Number 10905
ISO 9001: 2008
ISO 14001: 2004
BS OHSAS 18001: 2007